

HANGING STRAP

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development.

FEATURES

- Lightweight
- Low cost
- High strength design
- Easy installation
- Helps eliminate rattling
- Supports flexible duct without damaging outer jacket
- Resistant to grease, oil, gasoline & acid
- Waterproof & airtight

DESIGNED FOR HANGING

- Flexible duct
- PVC vent duct
- Duct board systems
- Many lighter weight steel duct applications

Fasten Strap To Beams



For maximum strength: put the two ends together and fold it over before securing to the ceiling or joist.



	VINYL DURO STRAP	NOVA STRAP
FLAME SPREAD & SMOKE DEVELOPMENT:	N/A	Less Than 25 / Less Than 50
TENSILE STRENGTH:	Warp-70 lbs./In. Fill-70 lbs./In	Warp-70 lbs./In.; Fill-70 lbs./In
HEAT RESISTANCE:	200° F	200° F
TEAR STRENGTH:	Warp- 8 lbs./In. Fill-11 lbs./In	N/A
FABRIC:	Black vinyl coated polyester fill	Black Woven Polypropylene
TOTAL FABRIC THICKNESS:	.022" Approx.	.025" Approx.
QUANTITY PER CARTON:	10 rolls (Conveniently packaged in a dispenser box with cutting blade)	24 rolls per box
ADDITIONAL INFO:	N/A	Resistant to Grease, Oil, Gasoline and Acid.

Item #	Code	Description	Quantity
10181	VDS200C	Vinyl Duro Strap 1-1/2" x 200'	200 ft. Roll
10180	NS300	Nova Strap 1-3/4" x 300'	300 ft. Roll



Best Installation Practices

The Air Duct Council recommends supporting flex duct at manufacturers recommended intervals or no greater than 4'. Maximum centerline sag shall be no more than 1/2" per foot. Hanging Strap must be a minimum of 1-1/2" wide. For more information, please visit the Air Duct Council "Supporting Flexible Duct" section 4.6.

Duro Dyne Corporate Headquarters, Bay Shore, NY
 631-249-9000 • Fax: 631-249-8346
 Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
 www.durodyne.com • E-mail: durodyne@durodyne.com

