


INSULATED ACCESS DOORS

Access doors are used in duct systems for many reasons. Entry is often required to facilitate duct cleaning, examine equipment, or to test, repair, or troubleshoot system components.

Duro Dyne's Insulated Tab-Style Access Doors are newly redesigned to offer improved performance over the competition. The nesting interior panel and high quality gasketing ensures our door won't leak under low-moderate pressure. Available with hinged/cam or cam only operation, Duro Dyne's Insulated Access Doors are built to last.

FEATURES:

- 24 gauge galvanized steel construction
- 10 stock sizes from 6x6 through 24x24
- Integral frame with no open corners
- Nesting door design eliminates compression & minimizes air leakage
- Tested to 10''SP with minimal leakage
- Half inch wide gasketed frame for sealing integrity
- Doors insulated with one inch thick fiberglass
- No extra holes in the door requiring plug rivets
- Square tabs reduce risk of injury during installation



Cam Only



Hinged

DOOR SIZE	Hinged		Cam Only	
	ITEM#	CODE	ITEM#	CODE
4" x 4"	6100	DAD4x4	6130	DADC4x4
6" x 6"	6101	DAD6x6	6131	DADC6x6
8" x 8"	6102	DAD8x8	6132	DADC8x8
10" x 10"	6103	DAD10x10	6133	DADC10x10
12" x 12"	6104	DAD12x12	6134	DADC12x12
14" x 14"	6105	DAD14x14	6135	DADC14x14
16" x 16"	6106	DAD16x16	6136	DADC16x16
18" x 18"	6107	DAD18x18	6137	DADC18x18
20" x 20"	6108	DAD20x20	6138	DADC20x20
24" x 24"	6109	DAD24x24	6139	DADC24x24

Duro Dyne Corporate Headquarters, Bay Shore, NY
631-249-9000 • Fax: 631-249-8346

Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
www.durodyne.com • E-mail: durodyne@durodyne.com