

SUBMITTAL RECORD _____
 JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____



Submittal Form Conduit

DESCRIPTION

Conduit is used to support duct sizes over 48" or smaller duct in high pressure applications. Duro Dyne offers conduit in 1/2", 3/4", and 1" sizes in, 10 ft. lengths.

FEATURES

- Complies with UL 797 and ANSI C80.3
- Hot Dip Galvanized Conduit
- Q235 Steel - Galvanized

Size	Outside Diameter	Inner Diameter	Thickness	Minimum Weight	Length
1/2"	17.93 mm	16.23 mm	0.85 mm	1.03 kgs/ft	10'
3/4"	23.42 mm	21.52 mm	0.95 mm	1.52 kgs/ft	10'
1"	29.54 mm	27.34 mm	1.10 mm	2.23 kgs/ft	10'



In accordance with: SMACNA Third Edition 2005 internal conduit pressure tables.

ITEM#	CODE	DESCRIPTION
21099	MC1210	1/2in Thin Wall Conduit - 10ft Lengths
21100	MC3410	3/4in Thin Wall Conduit - 10ft Lengths
13051	MC0110	1in Thin Wall Conduit - 10ft Lengths

Duro Dyne Corporate Headquarters, Bay Shore, NY
 631-249-9000 • Fax: 631-249-8346

Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
 www.durodyne.com • E-mail: durodyne@durodyne.com



©2020 Duro Dyne Corporation
 Printed in USA 10/13/2020
 BO050032