



# DUROSEAL™

## DUCT CLOSURE MASTIC



### FEATURES:

- For use in Medium & High Velocity Systems
- Suitable for Indoor & Outdoor use
- Fire Resistive
- Water Based
- Meets LEED requirements for credit EQ 4.1

### Underwriters Laboratories, Inc.

Classified Adhesive Surface Burning Characteristics  
66H9 Applied to Inorganic Reinforced Cement Board

	<b>USC</b>
Flame Spread	5
Smoke Developed	5

**Underwriters  
Laboratories, Inc.®  
LISTED  
CONTROL NO. 2S04  
181B-M**

### Appearance & Color

Soft, creamy gray paste

### Coverage

Approx. 35 sq. ft./per gal., brushed

Approx. 30 lineal ft. of 1/4" dia. bead per 1/12 gal. cartridge when extruded.

### Weight Per Gallon

10.5 lb.

### Average Non-volatile

70% by weight

### Pressure/Sealing Classes

Meets the requirements of all SMACNA Pressure and Seal Classes.

**VOC** - 54 g/l

### Ordering Information

Item #	Code	Description	Weight (lbs.)
5096	EDS1	DuroSeal Gallon Pail	48
4 one gallon pails per master carton			
Item #	Code	Description	Weight (lbs.)
5095	EDSC	DuroSeal Cartridge	23
24 cartridges per master carton			

**Duro Dyne East Division, Bay Shore, NY**    **631-249-9000**    **Fax: 631-249-8346**  
**Duro Dyne Midwest Division, Fairfield, OH**    **513-870-6000**    **Fax: 513-870-6005**  
**Duro Dyne West Division, Santa Fe Springs, CA**    **562-926-1774**    **Fax: 562-926-5778**  
**Duro Dyne Canada, Lachine, Quebec, Canada**    **514-422-9760**    **Fax: 514-636-0328**  
**www.durodyne.com**    **E-mail: durodyne@durodyne.com**



© Duro Dyne Corp.  
Printed in USA 10/06