






INSULATION FASTENERS

PINS CROSS COMPARISON

Name	SSP - Gold Seal Pins	CP - Rib Pins®	BDEP - Target Pins®	CTC - Slope Pins®	FTC - Econo-Point Pins
Picture					
Feature	Heat activated adhesive secures pin to liner	Dished washers & ribbed nails for faster cooling	Patented aerodynamic embossed washer & a recessed nail head	Sloped washer for a more flushed quilt depression	Specially pointed nail to assure uniform welding. Flat washer - best fit for upper plate
Pin Diameter	.130 Diameter	.15" Diameter	.130" Diameter	.130" Diameter	.130" Diameter
Pin Length	1/2" - 4"	1/2" - 2"	1/2" - 2-1/8"	1/2" - 2"	1/2" - 2"
Washer Diameter	Diameter - 1.0"	Diameter - 1.0"	Diameter - 1.0"	Diameter - 1.0"	Diameter - 1.0"
Thickness	.015" - .017"	.015" - .017"	.015" - .017"	.015" - .017"	.015" - .017"
Packaging	1,000, 3,000 and 5,000	1,000, 3,000 and 5,000	3,000 and 5,000 Sold in Buckets	3,000 and 5,000	3,000 and 5,000



Scan for Insulation
Fasteners submittal

DD TECH INSTITUTE