



CL6-WC2



CL12-WC3



CL18-WC4

ITEM #	CODE	DESCRIPTION	Safe Working Load*+	Quantity Per Ctn.
30181	LC12K05WC2/CL6	WC2-CL6 Wire Rope X 5 ft. 1-1/2 in. Looped Cable w/CL6-WC2 Lock	10-75 lbs. (5-34 kg)	10/bag - 10 bags/ctn
30182	LC12K10WC2/CL6	WC2-CL6 Wire Rope X 10 ft. 1-1/2 in. Looped Cable w/CL6-WC2 Lock	10-75 lbs. (5-34 kg)	10/bag - 10 bags/ctn
30183	LC12K15WC2/CL6	WC2-CL6 Wire Rope X 15 ft. 1-1/2 in. Looped Cable w/CL6-WC2 Lock	10-75 lbs. (5-34 kg)	10/bag - 10 bags/ctn
30184	LC12K25WC2/CL6	WC2-CL6 Wire Rope X 25 ft. 1-1/2 in. Looped Cable w/CL6-WC2 Lock	10-75 lbs. (5-34 kg)	5/bag - 10 bags/ctn
30185	LC12K05WC3/CL12	WC3-CL12 Wire Rope X 5 ft. 1-1/2 in. Looped Cable w/CL12-WC3 Lock	25-150 lbs. (12-68 kg)	10/bag - 10 bags/ctn
30186	LC12K10WC3/CL12	WC3-CL12 Wire Rope X 10 ft. 1-1/2 in. Looped Cable w/CL12-WC3 Lock	25-150 lbs. (12-68 kg)	10/bag - 10 bags/ctn
30187	LC12K15WC3/CL12	WC3-CL12 Wire Rope X 15 ft. 1-1/2 in. Looped Cable w/CL12-WC3 Lock	25-150 lbs. (12-68 kg)	10/bag - 10 bags/ctn
30188	LC12K25WC3/CL12	WC3-CL12 Wire Rope X 25 ft. 1-1/2 in. Looped Cable w/CL12-WC3 Lock	25-150 lbs. (12-68 kg)	5/bag - 10 bags/ctn
30134	LC12K30WC3/CL12	WC3-CL12 Wire Rope X 30 ft. 1-1/2 in. Looped Cable w/CL12-WC3 Lock	25-150 lbs. (12-68 kg)	5/bag - 10 bags/ctn
30193	LC18K05WC4/CL18	WC4-CL18 Wire Rope X 5 ft. 1-1/2 in. Looped Cable w/CL18-WC4 Lock	25-250 lbs. (12-114 kg)	10/bag - 10 bags/ctn
30194	LC18K10WC4/CL18	WC4-CL18 Wire Rope X 10 ft. 1-1/2 in. Looped Cable w/CL18-WC4 Lock	25-250 lbs. (12-114 kg)	10/bag - 10 bags/ctn
30195	LC18K15WC4/CL18	WC4-CL18 Wire Rope X 15 ft. 1-1/2 in. Looped Cable w/CL18-WC4 Lock	25-250 lbs. (12-114 kg)	10/bag - 10 bags/ctn
30196	LC18K25WC4/CL18	WC4-CL18 Wire Rope X 25 ft. 1-1/2 in. Looped Cable w/CL18-WC4 Lock	25-250 lbs. (12-114 kg)	5/bag - 10 bags/ctn

*Safe Working Loads are based on a 5:1 Safety Factor.

+Hanging at angles will reduce the Safe Working Loads. Please see our 'Effects of Hanging at Angles' <http://www.durodyne.com/DTTesting.php>