



STRUT LOCK ASSEMBLY

The Strut Lock Assembly is a fast, lockable solution for installing Dyn-O-Strut in single and multi-tiered arrangements, for HVAC and cable management. It is ideal for the suspension of rectangular duct, chilled beams, cable tray, unit heaters, etc. The ability to pre-fit the assembly into the strut channel on the ground, allows for minimal time working at heights. A threaded release cylinder allows for time saving height adjustment.

- Works best in conjunction with Deep 1-5/8" x 1-5/8" Dyn-O-Strut and Shallow 13/16" x 1-5/8" Dyn-O-Strut
- Can be used with single or multi-tiered applications
- For vertical, static loads
- 4:1 Safety Factor
- Quick to install and adjust
- Kit includes Strut Lock, zinc plated washer, flat washer and strut nut
- Strut Lock can be installed on the open or flat side of strut



ITEM #	CODE	DESCRIPTION	PACKAGED	WORKING LOAD*
31080	DSL3Z	Strut Lock Assembly for use with WC3 Wire Rope	10 sets/bag	25-150 lbs. (12-68 kg)
31081	DSL4Z	Strut Lock Assembly for use with WC4 Wire Rope	10 sets/bag	25-225 lbs. (12-102 kg)

*Safe Working Loads are based on a 4:1 Safety Factor

**WARNING: Always ensure the anchor point or base material are suitable to support the intended load, at the installer's responsibility